



MowMaster Pitch Roller

This is what we can offer you!

- . It has a huge adjustable **sun shade** for operator comfort. This is attached to a mast that can be raised or lowered to suit operator and storage applications
- . The **rear main roller** is made from 25mm thick tube and is fully machined for 100% roundness. This is a major benefit for keeping your pitch as flat and consistent as possible. If the roller has any inconsistency in roundness, it will move your surface. The roller is mounted on huge 60mm bearings.
- . the **front roller** is in 2 sections for easy turning as is made from 10mm tube, fully machined also and combined with our unique steering which requires 6 turns of the wheel for a full lock, eliminates scuffing the turf and gives the operator greater control in keeping straight consistent lines.
- . **Weight and weight distribution** -Weight can be adjusted from 1500kg to 2100kg by simply adding water. The distribution of weight is approximately 78% over and on the rear roller, just where you need it?
- . **Traversing**- We combine a fwd/rev lever that can be either set for desired rolling speed or simply go to full power. The machine is capable in excess of 10km per hr. a fantastic transport feature.
- . **Transmission**- The simplest most h/duty setup you will find. Hydraulic setup is so simple and we have thought of everything. Release valve for freewheeling, gate valves for servicing and there is a massive torque limiter attached to the system that completely stops an operator from damaging the hydraulic motor if driven constantly harsh from fwd to rev and vice versa. The limiter cuts in and the drive completely slips. **"Bullet Proof"**
- . The **operator** has incredible viewing area from a fully adjustable, swivel seat, with suspension. No back breaking or neck twisting. The viewing area to the actual rollers make it perfect to keep a straight line. The engine is completely out of operator area. The exhaust emissions are even further away and the shear quietness of the 25hp Honda engine is unbelievable.



MOW MASTER

TURF EQUIPMENT

Rear drum – 900mm diameter, The roller has a wall thickness of 25 mm and is fully machined. With a rolling width of 900mm.

Roller is mounted on 60mm bearings.

Front rollers are 2 section, 10mm thick and fully machined. Rollers are mounted on 50mm bearings.

Front and rear roller scrapers.

Unique hydraulic steering.

Huge sun shade, fully adjustable on both height and width.

Exceptional operator viewing area all from fully adjustable suspension seat including swivel.

Easy operator controls with speed settings.

Total dry weight of machine is 1420kg and 1960kg water filled plus operator.

Weight dispersion – 78% over main roller means 1100kg down pressure on main roller. Possible down pressure of 1640kg + water filled.

Hydraulic transmission – variable up to 9km/hr.

Engine – 25hp V - Twin Honda.

Please note the viewing area the operator has on both rollers.



See us at:

www.mowmaster.com.au

Contact us:

Ph - (08) 9362 2755

Fax - (08) 9362 2415

Email - admin@mowmaster.com.au

